



# SAFETY DATA SHEET HUMA GRO® Cal-Mag

HMIS	
HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0
PPE	D

## SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION

<b>PRODUCT IDENTIFIER:</b> HUMA GRO® Cal-Mag	<b>Product#</b> 032
<b>GENERAL USE:</b> Used as a part of a plant nutrition program and in the production of plant nutrient products.	
<b>PRODUCT DESCRIPTION:</b> A slightly viscous, clear to slightly hazy, light amber liquid.	
<b>SUPPLIER INFORMATION:</b> Bio Huma Netics, Inc. 1331 W Houston Avenue Gilbert, AZ 85233	<b>EMERGENCY PHONE NUMBERS</b>
<b>For Additional SDS call:</b> PHONE: (480) 961-1220	
<b>CHEMTREC:</b> (In the USA) 800-424-9300 (International) 703-527-3887	

## SECTION 2: HAZARDS IDENTIFICATION

### HAZARDS OVERVIEW:

A slightly viscous, clear to slightly hazy, light amber strongly acidic liquid. The vapors, mists and liquid may be irritating or corrosive to all tissues contacted. Inhalation of mists may cause severe irritation or burns to the entire respiratory tract. Ingesting this product can be harmful or possibly fatal even if swallowed in a relatively small amount.



**CLASSIFICATION:** SKIN CORROSION – CATEGORY 1A

**SIGNAL WORD:** DANGER

**HAZARD STATEMENT:** H314; causes severe skin burns and eye damage

**PRECAUTIONARY STATEMENT:** P260; Do not breathe dusts/mist/vapors. P280; Wear protective gloves/protective clothing/eye protection/face protection P264; Wash hands thoroughly after handling

## SECTION 3: COMPOSITION & INFORMATION ON INGREDIENTS

COMPONENT	CAS #	OSHA HAZARD	WT %	ACGIH		OSHA	
				TLV <sub>(TWA)</sub>	STEL	PEL <sub>(TWA)</sub>	STEL
Calcium Nitrate	10124-37-5	Oxidizer; Eye, Skin & Respiratory Irritant; Toxic by Ingestion	36 ± 4	None	None	None	None
Magnesium Nitrate	10377-60-3	Corrosive; Eye, Skin & Respiratory Hazard; Lung toxin; Toxic by Ingestion	35 ± 4	NDA	NDA	NDA	NDA

NDA = No Data Available      N/A = Not Applicable

## SECTION 4: FIRST AID MEASURES

<b>INHALATION:</b>	If inhaled, immediately move to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; use the Holger Nielsen method (back pressure-arm lift) or proper respiratory device. If breathing is difficult, give oxygen. Call a physician.
<b>EYE CONTACT:</b>	In case of contact, immediately flush eyes with plenty of clean running water for at least 15 minutes, lifting the upper and lower lids occasionally. Remove contact lenses, if worn. Get medical attention immediately.
<b>SKIN CONTACT:</b>	In case of contact, immediately flush skin with plenty of clean running water for at least 15 minutes, while removing contaminated clothing and shoes. If burn or irritation occurs, call a physician.
<b>INGESTION:</b>	If swallowed, DO NOT induce vomiting, unless directed to do so by medical personnel. Get medical attention immediately. If victim is fully conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person.
<b>NOTE TO PHYSICIANS:</b>	This product may be corrosive to all tissues contacted. If inhaled, delayed pulmonary edema may occur. If ingested, consideration should be given to careful endoscopy as stomach or esophageal burns, perforations or strictures may occur. Careful gastric lavage with an endotracheal tube in place should be considered. (Avoid using carbonate / bicarbonate lavage solutions as they may liberate a large volume of Carbon Dioxide gas and that could possibly damage or rupture internal organs from the pressure.) Treat exposure symptomatically.

## SECTION 5: FIRE FIGHTING MEASURES

<b>Flashpoint and Method:</b>	This product does not flash.		
<b>Flammable Limits (in air, % by volume)</b>	<b>Lower:</b> Not applicable	<b>Upper:</b> Not applicable	
<b>Autoignition Temperature:</b>	Not applicable		
<b>GENERAL HAZARD:</b>	This product is an aqueous solution of an inorganic oxidizer. The health hazard is: <b>Corrosive (Acidic)</b> . This product may ignite or react with many substances. Dilute solutions of this product may also be corrosive. This product may produce hazardous vapors and hazardous decomposition products.		
<b>FIRE FIGHTING INSTRUCTIONS:</b>	<b>EXTINGUISHING MEDIA:</b> Flood with water. Use water spray or fog to cool the containers exposed to the heat of a fire.		
<b>FIRE FIGHTING EQUIPMENT:</b>	Fire fighters should wear full protective equipment, including self-contained breathing apparatus.		
<b>HAZARDOUS COMBUSTION PRODUCTS:</b>	When heated to dryness and decomposition, it emits toxic nitrogen oxides and calcium oxide, with trace or ultra-trace toxic oxide amounts, of phosphorus, potassium, sulfur, iron, zinc, manganese, magnesium, sodium and carbon.		

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>RELEASE TO LAND:</b>	Wearing recommended protective equipment and clothing, dike the spill and pick up the bulk of liquid using pumps or a vacuum truck, or absorb the liquid in sand or a commercial absorbent. Place in approved containers for recovery, disposal, or satellite accumulation. Neutralize the acidity, of the remaining liquid, using soda ash, lime, or other agent appropriate for neutralizing acidic liquids. Flush the spill area with water; collect the rinsates for disposal or sewer, as appropriate.
<b>RELEASE TO WATER:</b>	Wear recommended protective equipment and clothing if contact with hazardous material can occur. Stop or divert water flow. Dike contaminated water and remove for disposal and/or treatment. As appropriate, notify all downstream users of possible contamination.

## SECTION 7: HANDLING AND STORAGE

<b>STORAGE TEMPERATURE:</b>	Ambient	<b>STORAGE PRESSURE:</b>	Ambient
<b>GENERAL:</b>	Store in a cool, dry, well-ventilated area away from incompatible materials and products. Avoid storing this product in direct sunlight. Do not allow this product to contact eyes, skin or clothing. Wear recommended personnel protective equipment when handling this product. Do not breathe vapors, mists or aerosols. Use only with adequate ventilation. Do not ingest (drink) this product. Keep the container tightly closed when not in use. Wash thoroughly after handling this product.		

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

**CONTROL MEASURES:** Use a local or general, mechanical exhaust ventilation system capable of maintaining emissions, in the work area, below the OSHA-PEL, ACGIH-TLV or levels that may cause irritation.

### RECOMMENDED PERSONAL PROTECTIVE EQUIPMENT

**RESPIRATOR:** For exposure above the ACGIH-TLV, AIHA-WEEL or OSHA-PEL, wear a NIOSH-approved full facepiece or half mask air-purifying cartridge respirator equipped with a good mist / particulate filter cartridge or supplied air. **Note:** Always consult the respirator manufacturer's data when determining the suitability of respiratory protective devices prior to use.

**EYES:** Wear chemical goggles (recommended by ANSI Z87.1-1979), unless a full facepiece respirator is worn. **Note:** Always consult the protective eyewear manufacturer's data when determining the suitability of protective eyewear prior to use.

**GLOVES:** Wear Neoprene, Nitrile, Butyl Rubber or Natural Rubber gloves. **Note:** Always consult the glove manufacturer's permeation data when determining the suitability of gloves prior to use.

**CLOTHING & EQUIPMENT:** Wear a Neoprene, Nitrile, Butyl Rubber or Natural Rubber apron, or full protective clothing when handling this product. An eye wash station and safety shower should be available in the work area. **Note:** Always consult the clothing/equipment manufacturer's permeation data when determining the suitability of clothing/equipment prior to use.

**FOOTWEAR:** Wear Neoprene, Nitrile, Butyl Rubber or Natural Rubber boots. **Note:** Always consult the footwear manufacturer's permeation data when determining the suitability of footwear prior to use.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Clear to slightly hazy, light amber	<b>Bulk Density (pounds/ft<sup>3</sup>):</b>	Not applicable
<b>Physical State:</b>	Liquid	<b>Vapor Pressure:</b>	No data available
<b>Odor:</b>	Slight, acidic type	<b>Vapor Density (air=1):</b>	No data available
<b>Odor Threshold:</b>	No data available	<b>Evaporation Rate (n-Butyl Acetate=1):</b>	No data available
<b>Molecular Formula:</b>	Mixture	<b>VOC Content:</b>	Not applicable
<b>Molecular Weight:</b>	Not applicable	<b>% Volatile:</b>	Approximately 60
<b>Boiling Point:</b>	Greater than 100° C. (212° F.)	<b>Solubility in H<sub>2</sub>O:</b>	Complete
<b>Freezing/Melting Point:</b>	Less than 0° C. (32° F.)	<b>Octanol/Water Partition Coefficient:</b>	No data available
<b>Specific Gravity:</b>	1.39 – 1.47 @ 20° C.	<b>pH (as is):</b>	0.5 – 1.5
<b>Density (pounds/gallon):</b>	Approximately 12.25	<b>pH (1% solution):</b>	Less than 2.5

## SECTION 10: STABILITY AND REACTIVITY

**GENERAL:** This product is stable and hazardous polymerization will not occur.

**CONDITIONS TO AVOID:** Do not store this product below 50° F (10° C) or above 90° F (30° C)

**INCOMPATIBLE MATERIAL:** Caustics and alkali, all reducing agents, oxidizable inorganic compounds, turpentine, organic chemicals, carbides, sulfides, sulfites, cyanides, chlorine releasers, most metals (especially Aluminum, Magnesium, Zinc, etc.) and combustible materials.

**HAZARDOUS DECOMPOSITION PRODUCTS:** When heated to dryness and decomposition, it emits toxic oxides of nitrogen and calcium with trace or ultra-trace toxic oxide amounts of phosphorus, potassium, sulfur, iron, zinc, manganese, magnesium, sodium and carbon.

**SENSITIVITY TO MECHANICAL IMPACT:** This product is not sensitive to mechanical impact.

**SENSITIVITY TO STATIC DISCHARGE:** This product is not sensitive to static discharge.

## SECTION 11: TOXICOLOGICAL INFORMATION

<b>Components:</b>	<b><u>Calcium Nitrate</u></b>	<b><u>Magnesium Nitrate</u></b>
<b>Eye Contact:</b>	No data available	No data available
<b>Skin Contact:</b>	No data available	No data available
<b>Oral Rat LD<sub>50</sub>:</b>	302 mg/kg	5440 mg/kg
<b>Dermal Rabbit LD<sub>50</sub>:</b>	No data available	500 mg/24H Mild
<b>Inhalation Rat LC<sub>50</sub>:</b>	No data available	No data available
<b>Human Data:</b>	No data available	No data available
<b>Other Toxicological Data:</b>	No data available	No data available
<b>Carcinogenicity:</b>	No data available	No data available
<b>Teratogenicity:</b>	No data available	No data available
<b>Mutagenicity:</b>	No data available	No data available
<b>Synergistic Products:</b>	None reported	None reported
<b>Target Organs:</b>	Eyes, Skin, Lungs, & Gastrointestinal tract	Eyes and skin
<b>Medical Conditions Aggravated By Exposure:</b>	Skin, Respiratory or Gastrointestinal disorders	No data available

## SECTION 12: ECOLOGICAL INFORMATION

### ENVIRONMENTAL FATE:

This product is completely soluble in water and may significantly affect the pH of water. No specific environmental fate data is available. Inorganic products do not meet the definition of biodegradability.

### ENVIRONMENTAL CONSIDERATIONS:

The aquatic toxicity of this product is related to the pH of the water. For Rainbow trout, the reported LC<sub>50</sub> is about a pH of 4.0, for a 7-day bioassay. Some species may vary from this pH level but all are susceptible to acidic conditions.

## SECTION 13: DISPOSAL CONSIDERATIONS

**RCRA 40 CFR 261 CLASSIFICATION:** Corrosive

**U.S. EPA WASTE NUMBER/DESCRIPTION:** D002

If this product is disposed of as shipped, it meets the criteria of a hazardous waste as defined under 40 CFR 261 due to its corrosivity. If this product becomes a waste, it will be a hazardous waste which is subject to the Land Disposal Restrictions under 40 CFR 268 and must be managed accordingly. As a hazardous liquid waste, it must be disposed of in accordance with local, state, and federal regulations in a permitted hazardous waste treatment, storage, and disposal facility.

## SECTION 14: TRANSPORTATION INFORMATION

<b>DOT PROPER SHIPPING NAME:</b>	<b>Corrosive Liquid, n.o.s.</b> (Contains Nitric Acid)		
<b>Hazard Class:</b>	8	<b>UN Number:</b>	UN1760
<b>Primary Label:</b>	Corrosive	<b>Subsidiary Label(s):</b>	None
<b>Primary/Subsidiary Placards:</b>	Corrosive		
<b>DOT Reportable Quantity (RQ):</b>	1,000 pounds (Nitric Acid)	<b>RQ for Product:</b>	25,000 pounds (2,161 gallons)
<b>Marine Pollutant:</b>	No		
<b>2012 North American Emergency Response Guidebook No.:</b>	154		
<b>TDG PROPER SHIPPING NAME:</b>	<b>Corrosive Liquids, n.o.s.</b> (Contains Nitric Acid)		
<b>Hazard Class:</b>	8	<b>UN Number:</b>	UN1760
<b>Primary Label:</b>	Corrosive	<b>Subsidiary Label(s):</b>	None
<b>Primary/Subsidiary Placards:</b>	Corrosive		
<b>TDG Reportable Quantity (RQ): *</b>	At least 5kg or 5 liters		
<b>TDG Schedule XII:</b>	Not listed		
<b>Regulated Limit (RL): **</b>	50kg (Nitric Acid)	<b>RL for Product:</b>	1,250kg (901.9 liters)
<b>Other Shipping Information:</b>	None		

\* Canadian Transportation of Dangerous Goods Regulations (TDGR), Part IX, Table I, Quantities or levels for Immediate Reporting: releases of reportable quantities, RQ, that meet the definition of a "dangerous occurrence" (a threat to life, health, property, or the environment) must be reported to the appropriate authorities as outlined in TDGR 9.13(1) and 9.14(1). \*\* Reporting to Environment Canada is required for any releases exceeding the regulated limits, RL, of 9.2 materials (primary or secondary). The regulated limits are found in Schedule XIII of the TDGR.

## SECTION 15: REGULATORY INFORMATION

<b>COMPONENTS:</b>	<u>Calcium Nitrate</u>	<u>Magnesium Nitrate</u>
<b><u>OSHA Target Organs:</u></b>	Eyes, Skin, Lungs, & Gastrointestinal tract	No data available
<b><u>Carcinogenic Potential:</u></b>		
<b>Regulated by OSHA:</b>	No	No
<b>Listed on NTP Report:</b>	No	No
<b>Listed by IARC:</b>	No	No
IARC Group:	Not applicable	Not applicable
<b>ACGIH Appendix A:</b>	Not listed	Not listed
A1 Confirmed Human:	Not applicable	Not applicable
A2 Suspected Human:	Not applicable	Not applicable

### U.S. EPA Requirements

#### Release Reporting

##### CERCLA (40 CFR 302)

<b>Listed Substance:</b>	Not listed	Not listed
Reportable Quantity:	Not applicable	Not applicable
Category:	Not applicable	Not applicable
RCRA Waste No.:	Not applicable	None listed
<b>Unlisted Substance:</b>	Yes	Yes
Reportable Quantity:	100 pounds	100 lbs
Characteristic:	Ignitability	Ignitability
RCRA Waste No.:	D001	Not applicable

### SARA TITLE III

#### Section 302 & 303 (40 CFR 355):

<b>Listed Substance:</b>	Not listed	No
Reportable Quantity:	Not applicable	Not applicable
Planning Threshold:	Not applicable	Not applicable

## SECTION 15: REGULATORY INFORMATION (continued from page 4)

COMPONENTS:	<u>Calcium Nitrate</u>	<u>Magnesium Nitrate</u>
<b>Section 311 &amp; 312</b> (40 CFR 370):		
Hazard Categories (product):	Fire: <u>N</u> Sudden Release of Pressure: <u>N</u> Reactive: <u>N</u>	Acute Health: <u>Y</u> Chronic Health: <u>N</u>
Planning threshold:	10,000 pounds	10,000 pounds
<b>Section 313</b> (40 CFR 372):		
<b>Listed Toxic Chemical:</b>	Yes (Nitrate Compounds)	Yes (Nitrate Compounds)
Reporting Threshold:	10,000 pounds	10,000 pounds

### U.S. TSCA Status

<b>Listed</b> (40 CFR 710):	Yes	Yes
-----------------------------	-----	-----

### State Regulations

#### State of California: Safe Drinking Water and Toxins Enforcement Act, 1986 (Proposition 65):

Carcinogen:	No	No
Reproductive Toxin:	No	No

### Other Regulations

<b>State Right To Know Laws:</b>	MA, NJ, PA, CA
----------------------------------	----------------

### Canadian Regulations

<b>Product Information:</b>		
Controlled Product:	Yes	
WHMIS Hazard Symbols:	Oxidizing Material; Corrosive Material	
WHMIS Class & Division:	C; E	
<b>Ingredient Information:</b>		
IDL Substance:	No	Yes
DSL or NDSL Lists:	DSL	DSL

## SECTION 16: OTHER INFORMATION

<b>EPA Registration number:</b>	Not applicable
<b>Approved Product Uses:</b>	Used as a part of a plant nutrition program.

### Special Notes:

This product is not manufactured, or formulated to contain substances, which the State of California has found to cause cancer and/or birth defects or other reproductive harm.

#### Special instructions:

Store Cal-Mag in a cool, dry, well-ventilated area, out of direct sunlight and away from incompatible materials or products. Do not add this product to hypochlorite bleaches, chlorine sanitizers or chlorinated cleaners as this liberates toxic, corrosive Chlorine gas.

**SDS Revision Information:** Revised 11/15/17

**SDS Distributed by:** Bio Huma Netics, Inc.

<b>Prepared By:</b>	Frank S. Pidgeon, Sr. EHSS Director	<b>Date Prepared:</b>	March 15 <sup>th</sup> 2017
---------------------	-------------------------------------	-----------------------	-----------------------------

This Safety Data Sheet is provided as an information resource only. It should not be taken as a warranty or representation for which Bio Huma Netics, Inc. assumes legal liability. While Bio Huma Netics, Inc. believes the information contained herein is accurate and compiled from sources believed to be reliable, it is the responsibility of the user to investigate and verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with applicable federal, state, and local regulations.